

US-2000 AD

ULTRASONIC
TECHNOLOGY 



The US-2000 AD with ultrasonic technology is a powerful, proven and universally applicable banding machine. It is extremely robust, low-maintenance and energy-efficient. Thanks to its modular design, continuously adjustable band tension, numerous options and many different sheet sizes, it can process products of almost any size and with different properties. The US-2000 AD processes strip made of paper and film and, depending on the version, strip widths of 20, 30, 50 or 60 mm.

- ✓ *Universally and flexibly applicable*
- ✓ *Many different arch sizes available*
- ✓ *Plug and Play*
- ✓ *Easy to use*
- ✓ *Ultra-Sonic Technologie*

Standardbogengrößen im Überblick / *Standard arch sizes at a glance*

Breite x Höhe in mm

260 x 120 / 180 / 260

360 x 180 / 260 / 360 / 500

500 x 260 / 360 / 500

700 x 260 / 360 / 550

900 x 260 / 360 / 500 nur 30 mm Bandführung

1'300 x 750 nur 30 mm Bandführung

1'700 x 360 nur 30 mm Bandführung

Weitere Bogengrößen auf Anfrage

Bandbreiten: 20 / 30 / 50 mm Standard
 15 / 60 mm Optional

Width x Height in inch

10.24 x 4.72 / 7.09 / 10.24

14.17 x 7.09 / 10.24 / 14.17 / 19.69

19.69 x 10.24 / 14.17 / 19.69

27.56 x 10.24 / 14.17 / 21.65

35.43 x 10.24 / 14.17 / 19.69 only 1,18 inch belt guide

51.18 x 29.53 only 1,18 inch belt guide

66.93 x 14.17 only 1,18 inch belt guide

Additional arch sizes upon request

Band widths: 0.79 / 1.18 / 1.97 inch standard
 0.59 / 2.36 inch optional



The photocell is height-adjustable and is used to automatically trigger the banding process.

Technical specifications

Bandwidth

20 , 30 , 50 mm

Weight

100 kg

Arch size

260 x 180 / 260 mm

360 x 180 / 260 / 360 mm

500 x 260 / 360 / 500 mm

See website



Wide range of different arch sizes available.

More information

