



STR555

Advanced function with ergonomic slantwise control panel

Description

Elegant shape with special side lift table top and ergonomic slantwise control panel. DC motors direct driven create silent, fast speed and wide tension range strapping. Heating & Cooling time are both adjustable to ensure sealing performance under different tension situations.

Features

- Side lift table
- Reliable tension system :
 - Big main roller driven by DC Motor
 - Tension range from 5 to 40 kgs.
- Electronic outside tension control
- Easy for Cooling Time Adjustment
- Easy for Heater Temperature Adjustment
- Easy to access track guide and main roller
- Various strap thickness and width workable
 - Width from 5 mm, thickness from 0.4 mm
- Less mechanism parts, easy in maintenance
- Ergonomics right side slantwise panel control
- Efficient and silent: Faster strapping cycle with less noise

Specification

Cycle Time	2 sec / strap
Tension Range	5~40kgs
Strap Width	5,6,9,12,15.5 mm adjustment
Sealing Method	Heating element
Reel Inside Diameter	200, 230, 280mm specified
Power Supply	110/ 220/ 230/ 240V, 50/60Hz, 1PH
Table Height	777mm
Power Consumption	0.3kw
Machine Dimension	L900 x W583 x H777
Machine Weight	61 kgs

*Specification subject to change without notice

