

## **POPULAR OPTIONS**

- Wrap height extension for taller pallets
- Frame extension for larger than standard pallets
- Split base for variable pallet size
- > 30" film carriage

- Turntable weight capacity increase
- Scale package with digital weight indicator
- > Auto film cut
- > 59" diameter turntable

## **TECHNICAL SPECIFICATIONS**

> Turntable Speed Adjustable up to 16 RPM **Control Type** Full-Feature Semi-Automatic Max. Load Capacity 5.000 lbs Max. Load Height 80" Turntable Size 48" x 48" octagonal 9" from floor > Turntable Height Pre-Stretch Ratio 250% standard Max. Load Size 56" x 56" Electrical 115/1/60 15 amp Warrantv 3/5 years >

85"

97"

The X-TRETCH pre-stretch film carriage provides superior film economy, film tension and user safety.


- ✓ Uses 20" machine film
- ✓ Electronically adjustable film tension
- ✓ 250% film pre-stretch ratio, others available
- Maintenance free ball bearing carriage guide
- ✓ Automatic corner compensation
- ✓ Lifetime warranty on stretch rollers

The Robust PRO-GLIDE turntable support system is maintenance free and features superior weight capacity.

- ✓ Structural steel frame
- ✓ Forklift portable
- ✓ Flush with floor pit mountable
- ✓ Easy access to components
- √ 1/2 HP turntable drive motor
- ✓ Heavy duty turntable chain drive

The advanced and user-friendly DIGI-TECH control unit features unique functions to wrap any type of pallet


- ✔ Photo-eye automatic height detection
- Separate top and bottom wrap count 1-10
- ✓ Turntable soft start/stop
- Dual adjustable film carriage speed
- Reinforce wrap function
- ✓ Positive turntable home alignment
- Gentle wrap feature for light or unstable pallets



Mach I

Clearance Required

**Tower Height** 



☑ info@strapco.ca www.strapco.ca



