

POPULAR OPTIONS

- Standard loading ramp for pallet jack
- > Extended heavy duty ramp for electrical walkie
- Wrap height extension for taller pallets
- Frame extension for longer and wider pallets
- > Auto film cut
- > 30" film carriage
- > 70" diameter turntable

TECHNICAL SPECIFICATIONS

>	Turntable Speed	Adjustable up to 16 RPM
>	Control Type	Full-Feature Semi-Automatic
>	Max. Load Capacity	5,000 lbs
>	Max. Load Height	86"
>	Turntable Size	59" diameter
>	Turntable Height	3" from floor
>	Pre-Stretch Ratio	250% standard
>	Max. Load Size	56" x 56"
>	Electrical	115/1/60 15 amp
>	Warranty	3/5 years
>	Tower Height	85"
>	Clearance Required	97"

The X-TRETCH pre-stretch film carriage provides superior film economy, film tension and user safety.

- ✓ Uses 20" machine film
- Electronically adjustable film tension
- ✓ 250% film pre-stretch ratio, others available
- Maintenance free ball bearing carriage guide
- ✓ Automatic corner compensation
- ✓ Lifetime warranty on stretch rollers

The Robust PRO-GLIDE turntable support system is maintenance free and features superior weight capacity.

- ✓ Structural steel frame
- ✓ Forklift portable
- ✓ Flush with floor pit mountable
- ✓ Easy access to components
- √ 1/2 HP turntable drive motor
- ✓ Heavy duty turntable chain drive
- Maintenance free turntable support casters
- ✓ Heavy duty turntable chain drive

The advanced and user-friendly DIGI-TECH control unit features unique functions to wrap any type of pallet

- ✔ Photo-eye automatic height detection
- Separate top and bottom wrap count 1-10
- ✓ Turntable soft start/stop
- ✓ Dual adjustable film carriage speed
- Reinforce wrap function
- ✓ Positive turntable home alignment
- Gentle wrap feature for light or unstable pallets









