SONIC ROTARY ARM experience superior film economy **SONIC RTG SEMI-AUTOMATIC ROTARY ARM**

POPULAR OPTIONS

- > Wrap height extension for taller pallets
- > Platform scale with digital weight indicator
- > 30" film carriage
- > Safety guarding around wrap zone
- > Auto film cut
- > Arm speed increase

TECHNICAL SPECIFICATIONS

>	Arm Speed	Adjustable up to 16 RPM
>	Control Type	Full-Feature Semi-Automatic
>	Max. Load Height	84"
>	Max. Load Diameter	76"
>	Pre-Stretch Ratio	250% standard
>	Max. Load Size	54" x 54"
>	Electrical	115/1/60 15amp
>	Warranty	3/5 year limited

The X-STRETCH pre-stretch film carriage provides superior film economy, film tension and user safety


- ✓ Uses 20" machine film
- ✓ Electronically adjustable film tension
- ✓ 250% film pre-stretch ratio, others available
- Maintenance free ball bearing carriage guide
- ✓ Automatic corner compensation
- ✓ Lifetime warranty on stretch rollers

The Sonic RTG features an all steel robust frame and the rotary arm ring gear support requires very little maintenance

- ✓ Structural steel frame
- ✓ Gantry frame
- ✓ Easy access to components
- √ 1/2 HP turntable drive motor
- ✓ Heavy duty arm tower chain drive
- Heavy duty ring bearing arm support support casters

The versatile HMI touch screen allows for a quick setup to wrap various type pallet loads

- ✔ Photo-eye automatic height detection
- Separate top and bottom wrap count 1-10
- ✓ Rotary tower soft start/stop
- Dual adjustable film carriage speed
- ✓ Lockable wrap parameters acces
- Safety photo-eye in front of rotary tower
- ✓ Automatic rotary tower home position



SONIC RTG



₹ 3245Bd. Pitfield, Saint-Laurent, QC Canada H4S 1H3

514 683 0555

514 683 0557

